


Non-heating devices / heating devices

Non-heating device plugs and sockets 10 A / 250 V~ | 70 °C | 2-pole with earthing contact

#	
C14 non-heating device plug with earthing contact For cables up to 3G 1.00 mm ² , thermoplastic version Screw terminal, protective rubber sleeve and strain relief	
915.171	Black
915.271	White
915.971	Grey, similar to RAL7035
C14 non-heating device right-angled plug with earthing contact For cables up to 3G 1.00 mm ² , thermoplastic version Screw terminal, protective rubber sleeve and strain relief, cable exit to right	
915.172	Black
C13 non-heating device socket with earthing contact For cables up to 3G 1.00 mm ² , thermoplastic version Screw terminal, protective rubber sleeve and strain relief	
915.170	Black
915.270	White
915.970	Grey, similar to RAL7035
C13 non-heating device right-angled socket with earthing contact For cables up to 3G 1.00 mm ² , thermoplastic version Screw terminal, protective rubber sleeve and strain relief, cable exit to right	
915.173	Black
915.973	Grey, similar to RAL7035
C14 non-heating device built-in plug E Thermoplastic version with screw terminal	
917.170	Black
C13 non-heating device built-in socket F Thermoplastic version with screw terminal	
917.171	Black



915.271



915.270



915.973



917.170



917.171

Non-heating device plugs and sockets 16 A / 250 V~ | 70 °C | 2-pole with earthing contact

#	
C20 non-heating device plug Thermoplastic version With protective rubber sleeve, for cable mounting	
915.175	Black
C19 non-heating device socket For cables up to 3G 1.50 mm ² Thermoplastic version Protective rubber sleeve for cable mounting	
915.174	Black
C20 non-heating device built-in plug Thermoplastic version	
917.173	Black
C19 non-heating device built-in socket J Thermoplastic version	
917.172	Black



915.175



915.174



917.173



917.172



May only be supplied to end user pre-wired | Only to be wired by qualified technicians