



Connection terminal, 400A, 3p, flat/round

Part no. **K240/3**

Catalog No. **039255**

EL-Nummer (Norway) **4132418**

### Delivery program

Product range			General switchboard accessories
Product function			Accessories panel building
Accessories			Terminations
Accessories			Terminals, 160 – 1000 A
Rated insulation voltage	U <sub>i</sub>	V AC	1000
Description			Including labels for terminal marking U, V, W - X, Y, Z - L1, L2, L3 - T1, T2, T3 - PE, N, PEN,  Relationship of rated operational current → terminal capacity to IEC/EN 60439, VDE 0660 Part 500 or EN 50021 Outer terminal for round or sectoral conductor, other side for Cu strip
Rated operational current	I <sub>e</sub>	A	400
Pole			3

### Terminal capacity

Cu/Al cable			<ul style="list-style-type: none"> <li>Cu</li> <li> Round stranded</li> <li> Sectoral stranded</li> <li> Round solid</li> <li> Sectoral solid</li> <li>Al</li> <li> Round solid</li> <li> Sectoral solid</li> </ul>
			<ul style="list-style-type: none"> <li>1 x 50 - 240</li> <li>2 x 25 - 120</li> </ul>
Al cable			<ul style="list-style-type: none"> <li>Al</li> <li> Sectoral solid</li> </ul>
			<ul style="list-style-type: none"> <li>1 x 95 - 185</li> <li>2 x 50 - 95</li> </ul>
Copper band		mm	<ul style="list-style-type: none"> <li>6 x 16 x 0.8</li> <li>10 x 16 x 0.8</li> </ul>
			# copper strip
conductor			<ul style="list-style-type: none"> <li>25 x 15</li> <li> Cu bar</li> </ul>

**Notes** Conversion kits for strip terminal in cable connection available separately  
Terminal covers available separately

### Technical data ETIM 6.0

Energy distribution systems (EG000015) / Rail terminal bar (EC000275)			
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Rail terminal bar clamp (ec1@ss8.1-27-40-06-03 [ACO369008])			
Number of poles			3
Connection type			Screwing
Number of connections < 6 mm <sup>2</sup>			0
Number of connections 10 mm <sup>2</sup>			0
Number of connections 16 mm <sup>2</sup>			0
Number of connections 25 mm <sup>2</sup>			0
Number of connections > 25 mm <sup>2</sup>			6
Number of connections total			6
Mounting method			Screw

Height		mm	100
Width		mm	144
Depth		mm	115
Contact safe			Yes