



Busbar shroud section, 12-30x5, B=1m




Powering Business Worldwide™

Part no. BBC-FL5

Catalog No. 107173

EL-Nummer (Norway) 2465011

Delivery program

| | | | |
|-----------------------|--|----|--|
| | | |  |
| Product range | | | 60 mm system Compact system |
| Subrange | | | Bar covers |
| Material | | | Silicon free, chlorine free |
| Self-extinguishing | | | to UL 94 |
| Temperature resistant | | | to 110°C |
| Length | | mm | 1000 |
| For use with | | | 12 x 5 15 x 5 20 x 5 25 x 5 30 x 5 |
| For use with | | | All 5 mm thick flat busbars |

Technical data ETIM 8.0

| | | | |
|--|--|--|-------------------------|
| Energy distribution systems (EG000015) / Accessories/spare parts for busbars (EC002270) | | | |
| Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Busbar (accessories) (ecl@ss10.0.1-27-40-06-36 [AC0563011]) | | | |
| Type of accessory/spare part | | | Contact protection rail |
| Accessory | | | Yes |
| Spare part | | | Yes |

Approvals

| | | | |
|--------------------------------------|--|--|---|
| Product Standards | | | UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking |
| UL File No. | | | E300273 |
| UL Category Control No. | | | NMTR, NMTR7 |
| CSA File No. | | | 236217 |
| CSA Class No. | | | 3211-37 |
| North America Certification | | | UL listed, CSA certified |
| Conditions of Acceptability | | | Refer to approbation report |
| Specially designed for North America | | | No |
| Suitable for | | | Feeder circuits |
| Current Limiting Circuit-Breaker | | | Refer to approbation report |
| Max. Voltage Rating | | | 600 V AC |
| Degree of Protection | | | Feeder circuits |