


Alina 90° 2.2W, 3000K

Technical data

Amperage	350mA	
System effect	2.2W	
Light source	LED	
Colour temperature	3000 Kelvin	
Light intensity	195 Lumen	
Colour rendering	CRI>90	
Expected lifespan	50,000 hours	
Dimmable, how	Depends on driver	
Flicker free	Yes, according to the new Ecodesign / ErP directive (September 2021)	
SVM <0.4	Yes	
PstLM <1	Yes	
SDCM	≤3	
Beam angle	90°	
Carving dimensions	Ø55 mm	
Installation height	12 mm	
Exterior dimensions	Ø70 mm	
Possibility of through wiring	No	
IP-class	IP44 (is intended for installation in areas 1 and 2)	
Insulation class	Class III	
Material	Aluminium, plastic	
Environment	Indoors	
Warranty	2 years with Nordtronic driver	
Approvals	CE	





*The drawing is not drawn to scale

Product information

- Approved for installation directly in the insulation and flammable materials
- Low mounting depth
- Suitable for installation in porouse material
- Light weight
- Connector on the lamp housing
- Dimmable with Nordtronic LED driver
- Incl. 3 meter cable with plug in both ends
- Designed and developed in Denmark





2400





3000





Lumen






























Item no.	EAN no.	Colour	Front design
3111	5704629031111	Matt white	Round
3112	5704629031128	Brushed alu	Round

Accessories

Item no.	EAN no.	Variant
1872	5704629018723	LED Driver dimmable, 5-16W
1883	5704629018839	LED Driver non dimmable, 2-20W
1875	5704629018754	Extention cable 2 m
3121	5704629031210	Mounting ring matt white
3122	5704629031227	Mounting ring brushed alu