



A40-W600 LED 1000 HF 830

A bathroom luminaire with a plain and functional design. The luminaire body is manufactured in steel and the diffuser in triple extruded acrylic, with end caps in synthetic material. The luminaire is flexible and can be mounted both horizontally and vertically



Item No.	A40812262
GTIN	4741145194037
Stock status	A



Technical specifications

General	
Product shape	Linear

Technical Data	
Maximum TA (°C)	35
IP classification	44

Light Technical Data	
Light source	LED
Lumen Out (lm)	960
Lumen Per Watt (lm/W)	107
Lamp colour temp (K)	3000
Colour Rendering Index	80
MacAdams Step	3
Energy Class Light Source	C

Driver / Ballast	
Type of LED Driver	HF
Number of Driver	1

Lifetime	
LED Lifetime L90B50 Ta25 (h)	60 000
Lamp Lumen Maintenance Factor	0.90

Electrical Data	
Main Feed AC (V) Min	220
Main Feed Voltage AC max	240
Main Feed Frequency Min	50
Main Feed Frequency Max	60
Total Consumption (W)	9
Number Of Luminaire MCB 10B	22
Number Of Luminaire MCB 10C	37
Number Of Luminaire MCB 16B	36
Number Of Luminaire MCB 16C	60
Leakage Current (mA)	0.25

Optic	
Optic Name	OP - Opal diffuser in acrylic

Housing	
Body Material	Steel
Treatment housing	Galvanised
Body Colour	White

Dimensions	
Length (mm)	600
Width (mm)	57
Height (mm)	73
Item Net Weight (kg)	0.9384

Termination	
Termination	3×2×2.5mm ² Push In

Mounting	
Product Mounting	Wall Surface

Logistic Data	
Item Gross Weight (kg)	1.02

Illustrations

