

Junction box

Junction box, 73 mm

Type: AU8.73

GTIN: 6438199000435

(F) (S) (N) (E


The AU8 junction box is 73 mm high and has eight inlets for Ø 20 conduits. Two of the Ø 20 inlets are equipped with removable reducers for adjusting them to fit Ø 16 conduits. The box also has knock-outs for 4 side inlets and 4 bottom inlets. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (850 °C). Max amount of conductors 40pcs.

Technical specification

General Information

| Product ID: | 2TKA003967G1 |
|--------------------|-------------------------|
| Packing | |
| Package: | 40 |
| Unit: | PCS |
| ETIM Data | |
| Mounting method: | Flush mounted (plaster) |
| Shape: | Round |
| Construction type: | Cable junction box |
| Model: | Single |
| | |

Customer service puh. +358 10 222 1999 contact.center@fi.abb.com 



Product Card

Junction box, 73 mm



| Provided with revolving ring: | No |
|---|--|
| Connectable: | No |
| Equipped with: | None |
| Diameter: | 94 mm |
| Length: | 135 mm |
| Width: | 135 mm |
| Depth: | 135 mm |
| Inner depth: | 69 mm |
| Suitable for wall/board thickness: | 12 mm |
| For number of electric fittings: | 1 |
| Mounting switching equipment: | Screwing |
| With screws: | No |
| Housing feed-through by break-out opening: | Yes |
| Housing feed-through by seal membrane: | No |
| Housing feed-through by nozzle: | Yes |
| Housing feed-through by step membrane: | No |
| For tube diameter: | 20/25 mm |
| Pipe locking: | Yes |
| | |
| Pipe locking optional: | No |
| Pipe locking optional: Inlet from the rear: | No Yes |
| | |
| Inlet from the rear: | Yes |
| Inlet from the rear: Number of inlets: | Yes 8 |
| Inlet from the rear: Number of inlets: Number of included spouts: | Yes 8 8 |
| Inlet from the rear: Number of inlets: Number of included spouts: Material: | Yes 8 8 Plastic |
| Inlet from the rear: Number of inlets: Number of included spouts: Material: Halogen free: | Yes 8 8 Plastic Yes |
| Inlet from the rear: Number of inlets: Number of included spouts: Material: Halogen free: Surface protection: | Yes 8 8 Plastic Yes Untreated |
| Inlet from the rear: Number of inlets: Number of included spouts: Material: Halogen free: Surface protection: Colour: | Yes 8 8 Plastic Yes Untreated White |
| Inlet from the rear: Number of inlets: Number of included spouts: Material: Halogen free: Surface protection: Colour: Transparent cover: | Yes 8 8 Plastic Yes Untreated White No |
| Inlet from the rear:Number of inlets:Number of included spouts:Material:Halogen free:Surface protection:Colour:Transparent cover:Cover attachment: | Yes 8 8 Plastic Yes Untreated White No Snapped on |
| Inlet from the rear:Number of inlets:Number of included spouts:Material:Halogen free:Surface protection:Colour:Transparent cover:Cover attachment:Sealable: | Yes 8 8 Plastic Yes Untreated White No Snapped on |
| Inlet from the rear:Number of inlets:Number of included spouts:Material:Halogen free:Surface protection:Colour:Transparent cover:Cover attachment:Sealable:With screening: | Yes 8 8 Plastic Yes Untreated White No Snapped on No |
| Inlet from the rear:Number of inlets:Number of included spouts:Material:Halogen free:Surface protection:Colour:Transparent cover:Cover attachment:Sealable:With screening:Air tight: | Yes 8 8 Plastic Yes Untreated White No Snapped on No |
| Inlet from the rear:Number of inlets:Number of included spouts:Material:Halogen free:Surface protection:Colour:Transparent cover:Cover attachment:Sealable:With screening:Air tight:Clamp position fixed: | Yes 8 8 Plastic Yes Untreated Untreated White No Snapped on No No |

_

Customer service puh. +358 10 222 1999

contact.center@fi.abb.com

_

ABB Exchange

_

+358 10 22 11

Page 2 of 3



_

Customer service

_

puh. +358 10 222 1999 contact.center@fi.abb.com