
Product datasheet

HALOLINE PRO 48 W 230 V R7S

HALOLINE PRO | Double ended halogen lamps with tube base



- General illumination Entrance lighting Pathway lighting
Outdoor applications only in suitable luminaires Traffic areas Shops Restaurants, hotels and similar prestigious applications Offices, public buildings Ideal for emphasizing and accentuating the structure of a room

- Brilliant accent lighting Direct replacement for standard tubular halogen lamps Significantly lower CO2 emissions compared to standard version Lower thermal output (compared with the standard reference product) No transformer required Contains no mercury



Product datasheet

Technical data

Electrical data

Nominal wattage	48.00 W
Nominal voltage	230 V
Rated wattage	48.00 W
Claimed equiv. conventional lamp power	60 W


Photometrical data

Rated color temperature	2900 K
Light color (designation)	Warm White
Rated luminous flux	750 lm
Color rendering index Ra	100
Nominal luminous flux	750 lm
Color temperature	2900 K
Luminous flux	750 lm

Light technical data

Starting time	0.0 s
---------------	-------

Dimensions & weight



Diameter	12.0 mm
Overall length	74.9 mm
Length	74.9 mm
Outer bulb	T12
Product weight	5.50 g

Lifespan

Rated lamp life time	2000 h
----------------------	--------

Product datasheet

Additional product data

Base (standard designation)	R7s
Mercury-free	Yes
Product remark	Fuse protection with indicated values recommended acc. to IEC60357, EN60357/For outdoor applications and operation in damp locations special approved fixtures are required/Technical and light values are subject to be changed

Capabilities

Fuse, quick-acting	2.0 A
Burning position	Any
Dimmable	Yes

Certificates & standards


Energy efficiency class	G
Energy consumption	48 kWh/1000h

Country specific categorizations

ILCOS	HDG-48-230-R7s-74,9
Order reference	64684 48W 230V

Product datasheet

Light Distribution



HAL_ohne_UVS

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321977595	HALOLINE PRO 48 W 230 V R7S	Shipping carton box 20 Pieces Folding carton box	92 mm x 77 mm x 113 mm	0.80 dm ³	197.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany