

Product datasheet HALOLINE PRO 80 W 230 V R7S

HALOLINE PRO | Double ended halogen lamps with tube base



- General illumination Entrance lighting Pathway lighting Outdoor applications only in suitable luminaires Traffic areas Shops Restaurants, hotels and similar prestigious applications Offices, public buildings Ideal for emphasizing and accentuating the structure of a room

 Brilliant accent lighting Direct replacement for standard tubular halogen lamps Significantly lower CO2 emissions compared to standard version Lower thermal output (compared with the standard reference product) No transformer required Contains no mercury



Technical data

Electrical data

Nominal wattage	80.00 W
Nominal voltage	230 V
Rated wattage	80.00 W
Claimed equiv. conventional lamp power	100 W

Photometrical data


Rated color temperature	2900 К
Light color (designation)	Warm White
Rated luminous flux	1400 lm
Color rendering index Ra	100
Nominal luminous flux	1400 lm
Color temperature	2900 К
Luminous flux	1400 lm

Light technical data

Starting time

0.0 s

Dimensions & weight



Diameter	12.0 mm
Overall length	74.9 mm
Length	74.9 mm
Outer bulb	T12
Product weight	5.60 g

Lifespan

Rated lamp life time	2000 h

Additional product data

Base (standard designation)	R7s		
Mercury-free	Yes		
Product remark	Fuse protection with indicated values recommended acc. to IEC60357, EN60357/For outdoor applications and operation in damp locations special approved fixtures are required		

Capabilities

Fuse, quick-acting	2.0 A	
Burning position	Any	
Dimmable	Yes	


Certificates & standards

Energy efficiency class	G
Energy consumption	80 kWh/1000h

Country specific categorizations

ILCOS	HDG-80-230-R7s-74,9	
Order reference	64690 80W 230V	

Light Distribution



HAL_ohne_UVS

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321928078	HALOLINE PRO 80 W 230 V R7S	Shipping carton box 20 Pieces Folding carton box	112 mm x 77 mm x 92 mm	0.79 dm³	209.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany