

Product datasheetP RF CLAS A DIM 7 W/827 E27

PARATHOM Retrofit CLASSIC A DIM | Dimmable LED lamps, classic bulb shape



 Perfect for decorative installations Domestic applications General illumination Outdoor use in outdoor luminaires only (minimum IP65)

Design, dimensions, luminous flux comparable to an incandescent or halogen lamp Very low energy consumption Robust
against vibrations No UV and near-IR radiation in the light beam Instant 100 % light, no warm-up time No UV and near-IR
radiation in the light beam Can be easily fitted instead of ordinary light bulbs





Product datasheet

Technical data

Electrical data

| Rated wattage | 7.00 W |
|--|----------|
| Nominal wattage | 7.00 W |
| Nominal voltage | 220240 V |
| Operating frequency | 5060 Hz |
| Max. lamp no. on circuit break. 10 A (B) | 306 |
| Max. lamp no. on circuit break. 16 A (B) | 490 |
| Nominal current | 0.044 A |
| Claimed equiv. conventional lamp power | 60 W |


Photometrical data

| Nominal luminous flux | 806 lm |
|---|------------|
| Rated luminous flux | 806 lm |
| Rated color temperature | 2700 K |
| Color rendering index Ra | ≥80 |
| Light color (designation) | Warm White |
| Standard deviation of color matching | ≤6 sdcm |
| Color temperature | 2700 K |
| Luminous flux | 806 lm |
| Lumen main.fact.at end of nom.life time | 0.70 |

Light technical data

| Beam angle | 320.00 ° |
|---------------|----------|
| Starting time | < 0.5 s |

Dimensions & weight



| Overall length | 105.0 mm |
|----------------|----------|
|----------------|----------|

Product datasheet

| Diameter | 60.0 mm |
|----------------|----------|
| Outer bulb | A60 |
| Product weight | 32.00 g |
| Length | 105.0 mm |

Temperatures & operating conditions

| Ambient temperature range | -20+40 °C |
|---------------------------|-----------|
| | |

Lifespan

| Nominal lamp life time | 15000 h |
|--|---------|
| Rated lamp life time | 15000 h |
| Number of switching cycles | 100000 |
| Lumen maintenance at end of service life | 0.70 |

Additional product data

| Base (standard designation) | E27 |
|-----------------------------------|--|
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Appropriate disposal acc. to WEEE | Yes |
| Successor EAN | 4058075591295 |
| Product remark | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance) |
| Predecessor EAN | 4058075287402, 4058075439412 |

Capabilities

| Dimmable | Yes |
|----------|-----|
|----------|-----|

Certificates & standards

| Energy efficiency class | Е |
|-------------------------|-------------|
| Energy consumption | 7 kWh/1000h |
| Type of protection | IP20 |

Product datasheet

Country specific categorizations

| Order reference | LEDPCLA60D 7W/8 |
|-----------------|-----------------|
|-----------------|-----------------|

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|--------------------------------|--|--------------------------------------|----------------------|--------------|
| 4058075439412 | P RF CLAS A DIM 7 W/827 E27 | Shipping carton box 10 Pieces Folding carton box | 325 mm x 136 mm x 126 mm | 5.57 dm ³ | 553.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS



OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany