



Auxiliary contact, 1N/O+1N/C, 8 A, 250 V AC

Part no. Z-HK
Catalog No. 248432

EL-Nummer (Norway) 1609487

Delivery program

Basic function		Accessories for residual current circuit-breakers
Basic function accessories		Auxiliary contacts
Application		Switchgear for industrial and advanced commercial applications
Product range		Accessory
Side mounting		for fitting on left to: FI
Contact sequence		

Technical data

Electrical

Contact function			1 NO + 1 NC
Rated operational voltage	U_e	V AC	250
Rated frequency	f	Hz	50/60
Rated current	I_e	A	8
Conventional free air thermal current	I_{th}	A	8
Rated operational current			
AC--13			
250 V	I_e	A	6
DC-13	I_e	A	2 (110V DC)
Minimum operating voltage per contact	U_{min}	V DC	24
Rated impulse withstand voltage	U_{imp}	kV	2.5

Mechanical

Mounting width		mm	8.8 (0.5 SU)
Degree of protection			
Integrated			IP40
Terminals			Lift terminals
Tightening torque of terminal screws		Nm	≤ 1.0

Design verification as per IEC/EN 61439

Technical data for design verification		
--	--	--

Operating ambient temperature min.	°C	-5
Operating ambient temperature max.	°C	40

Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)

Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss10.0.1-27-14-35-02 [AKE327013])

Device fitting		Earth leakage switch
Additional equipment		Auxiliary switch
Installed at the factory		No
Width in number of modular spacings		0.5
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		0
Number of fault-signal switches		0
Rated switch current	A	3
Rated voltage	V	230
Voltage type for actuating		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		2
Suitable for max. current main contact unit	A	8

Dimensions

