




**Auxiliary contact, for PLS, postal Code, PKNM, ZP-A40, ZP-ASA, Z-MS, 2W, 0.5HP**

**Part no. ZP-NHK**  
**Catalog No. 248437**

**EL-Nummer 1609489**  
**(Norway)**

### Delivery program

Basic function		Accessories for combined residual-current/power circuit-breakers Accessories for miniature circuit-breaker
Basic function accessories		Tripping signal contacts
Application		Switchgear for industrial and advanced commercial applications
Product range		Accessory
Side mounting		for fitting on left to: LS, FI/LS
Contact sequence		

### Technical data

#### Electrical

Contact function			2 CO
Rated operational voltage	$U_e$	V AC	250
Rated frequency	f	Hz	50/60
Rated current	$I_e$	A	4
Conventional free air thermal current	$I_{th}$	A	4
Rated operational current			
AC--13			
250 V	$I_e$	A	3
AC-15	$I_e$	A	2 (250 V AC)
Minimum operating voltage per contact	$U_{min}$	V DC	5
Rated impulse withstand voltage	$U_{imp}$	kV	2.5

#### Mechanical

Mounting width		mm	8.8 (0.5 SU)
Degree of protection			
Integrated			IP40
Terminals			Lift terminals
Tightening torque of terminal screws		Nm	≤ 1.0

### Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-5
Operating ambient temperature max.		°C	40

### Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)

Device fitting			Universal
Additional equipment			Signalling switch
Installed at the factory			No
Width in number of modular spacings			0.5
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Number of contacts as change-over contact			2
Number of fault-signal switches			0
Rated switch current		A	4
Rated voltage		V	250
Voltage type for actuating			AC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			2
Suitable for max. current main contact unit		A	4

## Dimensions

