DATASHEET - Z-PUL230/SS



Pushbutton with LED, 230AC/DC, 2N/O, 16A, orange, 1HP

Part no. Z-PUL230/SS Catalog No. Z-PUL230/SS



Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	In	Α	16
Heat dissipation per pole, current-dependent	P _{vid}	W	2
Equipment heat dissipation, current-dependent	P _{vid}	W	4

Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Push button for distribution board (EC001546)

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Push button for distribution board (ect@ss10 0 1-27-14-23-02 [AF7814014])

(ecl@ss10.0.1-27-14-23-02 [AFZ814014])		
Number of contacts as normally closed contact		0
Number of contacts as normally open contact		2
Number of contacts as change-over contact		0
Switching current	А	16
Switching voltage	V	250
Voltage type		AC
With signal lamp		Yes
Colour calotte		Other
Lamp type		LED
Lamp socket		Other
Max. lamp power	W	2
Lamp voltage	V	110 - 240
Colour button		Green
Width in number of modular spacings		1
Built-in depth	mm	60
Degree of protection (IP)		IP40