



Transformator 230V, 12/24V, 2/1A, 3HP

Part no. TR-G2/24  
 Catalog No. 272484

Similar to illustration

**Design verification as per IEC/EN 61439**

Technical data for design verification			
Rated operational current for specified heat dissipation	$I_n$	A	0
Heat dissipation per pole, current-dependent	$P_{vid}$	W	0
Equipment heat dissipation, current-dependent	$P_{vid}$	W	7.92
Static heat dissipation, non-current-dependent	$P_{vs}$	W	0
Heat dissipation capacity	$P_{diss}$	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	35
			0

**Technical data ETIM 8.0**

Devices for distribution board-/surface mounting (EG000062) / Bell transformer (EC001547)			
Electric engineering, automation, process control engineering / Transformer, converter, coil / Bell transformer / Bell transformer (unspecified) (ecl@ss10.0.1-27-03-11-90 [BAC147011])			
Primary voltage		V	230
Secondary voltage 1		V	12
Secondary voltage 2		V	24
Secondary voltage 3		V	0
Secondary amperage 1		A	2
Secondary amperage 2		A	1
Secondary amperage 3		A	0
Max. output power		W	0
Max. output current		A	0
Max. power loss		W	0
Type of transformer			Standard bell ringing transformer
Surface mounting			Yes
Flush-mounted installation			No
Modular version			Yes
Length		mm	55
Width		mm	54
Height		mm	90
Width in number of modular spacings			3
Short-circuit protected			Yes
Temperature protection			Yes
With on/off switch			No