LUNA 127 star S Item no.: 1270900

theben

Time and light control Twilight switches

Description

- Twilight switch with integrated light sensor
- Test function
- Teach-in function
- Timer function (1 hour on)
- Switchable brightness range: 2-100/100-2000 lux
- Cable feed from the back and from below
- Cover with snap-on function when opening for the straightforward installation of the device
- Captive screws
- Large terminal area
- Brightness value can be set without opening the device
- Large light exposure angle (approx. 180 degrees)



Technical data

	LUNA 127 star S
Operating voltage	230 V AC
Frequency	50 – 60 Hz
Number of channels	1
Stand-by consumption	~0.7 W
Setting range brightness	2 – 2000 lx
Switch-on delay	2 – 100 s
Switch-off delay	2 – 100 s
Type of contact	NO contact
Switching output	Not potential-free (230 V)
Installation type	Wall installation or mast bracket

	LUNA 127 star S
Type of connection	Screw terminals
Switching capacity	16 A at 230 V AC, cos φ = 1, 10 AX at 230 V AC, cos φ = 0.3
Incandescent/halogen lamp load	2300 W
Halogen lamp load	2300 W
LED lamp < 2 W	50 W
LED lamp 2-8 W	600 W
LED lamp > 8 W	600 W
Housing and insulation material	High-temperature resistant, self- extinguishing thermoplastic
Ambient temperature	-35°C 55°C





Technical data

	LUNA 127 star S
Type of protection	IP 55
Protection class	II

Connection example



LUNA 127 star S Item no.: 1270900



Scale drawings



Accessories

Adapter plate LUNA star Item no.: 9070486



LUNA star adapter mast fixing Item no.: 9070793

