


386100240060

Relay interface module



Technical description: Relay interface modules, Electromechanical relay, with screwless terminal, 1 pole, CO (nPDT), 6 A, AgNi, AC/DC coil, 24 V, operating from 19.2 to 26.4 V (AC)/(DC), rated power 0.3 VA (AC) / 0.2 W (DC), consumption 12 mA, holding voltage 14.4 V (AC)/(DC), must drop-out voltage 2.4 V (AC) and 1.2 V (DC), option: AC or AC/DC, version: CO (nPDT), ambient temperature from -40 to +55 °C

Commercial description: Electromechanical relay interface module with screwless terminals, 1 CO rated 6 A/250 V AC, 6.2 mm wide, 35 mm rail (EN 60715) mounting, for PLC or other systems.

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-40...55 °C
Contact configuration:	1 pole, CO (nPDT)
Dimension:	6.2x93.6x72.5 mm
Electrical life:	60000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage ac:	24 V
Nominal voltage dc:	24 V
Operating range ac:	19.2...26.4 V
Operating range dc:	19.2...26.4 V
Rated current contact:	6 A
Rated power ac:	0.3 VA
Rated power dc:	0.2 W
Rated voltage contact:	250 V AC
Supply version:	AC/DC coil
Type:	Electromechanical relay, with screwless terminal

Certifications and quality approvals (according to code):



Need more information?

[Contact our sales](#) [Find a dealer](#)