


386102400060

Relay interface module



Technical description: Relay interface modules, Electromechanical relay, with screwless terminal, 1 pole, CO (nPDT), 6 A, AgNi, DC coil, 220 V, operating from 176 to 264 V, rated power 0.9 W, consumption 4 mA, holding voltage 144 V, must drop-out voltage 12 V, option: AC or AC/DC, version: CO (nPDT), ambient temperature from -40 to +55 °C

Commercial description: Electromechanical relay interface module with screwless terminals, 1 CO rated 6 A/250 V AC, 6.2 mm wide, 35 mm rail (EN 60715) mounting, for PLC or other systems.

[BROWSE PRODUCT PAGE](#)

Technical Features:

| | |
|----------------------------|--|
| Ambient temperature range: | -40...55 °C |
| Contact configuration: | 1 pole, CO (nPDT) |
| Dimension: | 6.2x93.6x72.5 mm |
| Electrical life: | 60000 cycles |
| Insulation coil/contacts: | 6 kV |
| Nominal voltage dc: | 220 V |
| Operating range dc: | 176...264 V |
| Rated current contact: | 6 A |
| Rated power dc: | 0.9 W |
| Rated voltage contact: | 250 V AC |
| Supply version: | DC coil |
| Type: | Electromechanical relay, with screwless terminal |

Certifications and quality approvals (according to code):



Need more information?

[Contact our sales](#) [Find a dealer](#)