

403190240000

Miniature pcb plug in relay



Technical description: Miniature PCB Relays, PCB/Plug-in – 3.5 mm pinning, 1 pole, CO (nPDT), 12 A, AgNi, DC coil, 24 V, operating from 17.5 to 36 V, rated power 0.65 W, resistance 900 Ω, consumption 27 mA, holding voltage 9.6 V, must drop-out voltage 2.4 V, option: Pin length 5.3 mm (Plug-in relays), version: Flux proof (RT II), ambient temperature from -40 to +85 °C

Commercial description: Miniature PCB relay, 1 CO 12 A. PCB mount (3.5 mm pin pitch) or plug-in with 95 Series sockets, DC coils (650 mW or 500 mW) and AC coils. Variant with Cadmium-free contacts. 8 mm, 6 kV (1.2/50 μs) insulation between coil and contacts. Complies with the glow wire test according to EN 60335-1..

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-40...85 °C
Contact configuration:	1 pole, CO (nPDT)
Dimension:	12.4x25x29 mm
Electrical life:	200000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage dc:	24 V
Operating range dc:	17.5...36 V
Rated current contact:	12 A
Rated power dc:	0.65 W
Rated voltage contact:	250 V AC
Supply version:	DC coil
Type:	PCB/Plug-in – 3.5 mm pinning

Certifications and quality approvals (according to code):



Need more information?

[Contact our sales](#) [Find a dealer](#)