

## 703184002022


### Line monitoring relay

**Technical description:** Electronic voltage monitoring relays, 3 phase AC line monitoring, 1 pole, 6 A, AC supply version, nominal voltage 400 V, operating from 220 to 510 V, rated power 11 VA, Detection values: 2 adjustable detection values, CO (nPDT), Time delay setting: Adjustable switch-off delay, Fault memory option: Fault memory function selectable, ambient temperature from -20 to +60 °C

**Commercial description:** Line voltage monitoring relay for three-phase networks. Multi-function model for monitoring three-phase (380 ... 415)V undervoltage, overvoltage, window mode (overvoltage + undervoltage), phase rotation and phase loss (detects phase loss error even in the presence of regenerated voltages) Voltage fault memory – selectable.

[BROWSE PRODUCT PAGE](#)

#### Technical Features:

Ambient temperature range:	-20...60 °C
Contact configuration:	1 pole, CO (nPDT)
Dimension:	35x84x56.5 mm
Nominal voltage:	400 V
Operating range ac:	220...510 V
Rated current contact:	6 A
Rated voltage contact:	250 V AC
Supply version:	AC supply version
Type:	3 phase AC line monitoring
Certifications and quality approvals (according to code):	  

#### Need more information?

[Contact our sales](#) [Find a dealer](#)