



A3 female 3-pole, screw t., 400 V, 10 A

A3
Female
3-pole
Screw terminal
Technical data will be only guaranteed with Murrelektronik components.

Link to Product

Illustration



Product may differ from Image

Technical Data	
Operating voltage	400 V AC/DC
Rated surge voltage	4.0 kV
Operating current	10 A
No. of poles	3 + PE
Material group	IIIb
Mating cycles	min. 500
Connection	Screw terminal
Connection cross section	0.5...1.5 mm²
Pull-out force	min. 40 N
Holding force	> 150 N
Tightening torque (clamp screw)	min. 0.2 Nm

Insertion and withdrawal force	< 100 N
Stripping length	5 mm
Isolation resistance	$\geq 10^8 \Omega$
Contact resistance	$\leq 5 \text{ m}\Omega$
Over voltage category	III
Wire-Ø incl. isolation	max. 4 mm

General data

Material (contact)	Brass
Material (contact surface)	Ag
Pollution Degree	3
Temperature range	-40...+125 °C
Material (contact carrier)	PA GF
Flammability class	V-0 (acc. to UL 94)
Size	A3
Type	Female
Climatic category	40/125/21
Dimensions H×W×D	26×21×21 mm

Cables

Current load capacity	see derating curve
Product article number of manufacturer	70MH-EB003-AS02010