

TREE 8TX Eco Gigabit Unmanaged Switch

8 port Gigabit unmanaged Switch Connection cables are in the online shop under "Connection Technology".

Link to Product

Illustration



Product may differ from Image



Technical Data	
Operating voltage	2× 930 V DC, redundancy
Transfer rate	10/100/1000 Mbit/s full duplex
Over voltage protection	yes
Operating current (switch)	max. 450 mA
Operating modes	Autocrossing Autonegotiation
Invers-polarity protection	yes
General data	
Mounting method	DIN-rail mountable TH35 (EN 60715)
Temperature range	0+60 °C (storage temperature -10+70 °C)
Housing	Black plastic
Protection	IP20
Dimensions H×W×D	90×45.2×78 mm
Connections	
Fieldbus	8× RJ45
Supply	Screw plug-in terminal: 0.21.5 mm ²
Switch Management	
Protocols	no
Port Mirroring	no
VLAN (QoS) IEEE 802.p	yes
Alarm contact	no
Remote maintenance	no
Webserver	no
Switch Form	Unmanaged Switch

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2023-02-10

Murrelektronik GmbH | Falkenstraße 3 | 71570 Oppenweiler | Fon +49 (71 91) 47-0 | Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com



Product article number of manufacturer	58176
Diagnostic	
Communication status	via LED
Monitoring - no voltage	yes

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2023-02-10

Murrelektronik GmbH | Falkenstraße 3 | 71570 Oppenweiler | Fon +49 (71 91) 47-0 | Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com