

EK 60 UNV Battery-powered hydraulic universal tool 6 - 300 mm<sup>2</sup>

NEXT GENERATION



- ▶ One head for crimping, cutting and punching - one tool for all
- ▶ Ideal in the assembly field where all common jobs can be carried out using one tool
- ▶ Fast working due to 2-stage hydraulics
- ▶ All tool data on view thanks to display and i-press® app

**Characteristics**

- Choose your battery system: Bosch or Makita
- All data can be easily read via Bluetooth
- Universal head flip top style, rotatable
- Simple and safe: One-button operating concept for controlling all tool functions
- Effortless working due to balanced centre of gravity
- LED for work area illumination
- Simple and safe: Automatic retraction when operation is complete (crimping or cutting)
- Always ready-to-use thanks to battery charge and service display

**Technical instructions**

- Interchangeable adapters and dies for crimping, cutting and punching you will find on page 478
















Technical data			
Crimping force	60 kN		
Stroke	42 mm		
Crimping range	6 - 300 mm <sup>2</sup>		
Crimping cycle	3 s to 5 s (depending on cross-section)		
Cutting range	max. 40 mm dia.		
Punching capacity	up to 64 mm dia. round		
Charging time	45 min.		
Weight	4.8 kg		
Ambient temperature	-10 °C up to +40 °C		
Item	Part No. Bosch	Part No. Makita	
Battery-powered hydraulic universal tool 6 - 300 mm <sup>2</sup>	<b>EK60UNVCFB</b>	<b>EK60UNVCFM</b>	
Scope of supply			Page
Bosch battery 18 V / 5.0 Ah, Li-Ion	RALB2EU		493
Bosch quick-charger for 18 V Li-Ion battery	LGLB1EU		494
Makita battery 18 V / 4.0 Ah, Li-Ion	RAL40		492
Makita quick-charger for 18 V Li-Ion battery	LGL1		494
Plastic case 450 x 370 x 105 mm	UA22	UA22	478
Adapter for crimping dies of Series 22	KK120UNVNG	KK120UNVNG	

3



### Interchangeable adapters and dies for crimping, cutting or punching

Part description	Part no.	Tools		
		6 ton	12 ton	
<b>Application: crimping</b>				
 Adapter for crimping dies series 5	UA5	●		
 Adapter for crimping dies series 13	UA12TKL		●	
 Adapter for crimping dies series 18	UA18	●		
 Adapter for crimping dies series 22	UA22	●		
<b>Application: cutting</b>				
 Cutting die for Al/Cu conductors to max. 40 mm dia.	UCACSR	●	●	
 Cutting die for Al/Cu conductors to max. 26 mm dia. (Not suitable for fine and superfine stranded conductors)	UC26	●	●	
	Cutting die for Al/Cu conductors to max. 40 mm dia. (Not suitable for fine and superfine stranded conductors)	UC40	●	●
 Cutting die for threaded rods M5 metric	UCM5	●	●	
	Cutting die for threaded rods M6 metric	UCM6	●	●
	Cutting die for threaded rods M8 metric	UCM8	●	●
	Cutting die for threaded rods M10 metric	UCM10	●	●
	Cutting die for threaded rods M12 metric	UCM12	●	●
	Cutting die for threaded rods 1/4"	UCUNC14	●	●
	Cutting die for threaded rods 3/8"	UCUNC38	●	●
	Cutting die for threaded rods 1/2"	UCUNC12	●	●
 Cutting die for profile conductors 35 x 15	UCD3515	●	●	
	Cutting die for profile conductors 32 x 15 x 9	UCD3215	●	●
	Cutting die for profile conductors 35 x 7.5	UCD3575	●	●
 Cutting die for profile conductors 2980	UCN2980	●	●	
 Cutting die for laminated Cu bus bars, max. width 37.5 mm	UCF	●		
 Cutting die 107 mm <sup>2</sup> type AC for catenary wires in railway construction	UCAC107	●	●	
	Cutting die 85 mm <sup>2</sup> type BC for catenary wires in railway construction	UCBC85	●	●
	Cutting die 110 mm <sup>2</sup> type BC for catenary wires in railway construction	UCBC110	●	●
	Cutting die 120 mm <sup>2</sup> type BC for catenary wires in railway construction	UCBC120	●	●
	Cutting die 150 mm <sup>2</sup> type BC for catenary wires in railway construction	UCBC150	●	●
<b>Application: Punching</b>				
 Hole punch adapter for holes to 64 mm dia., 92 x 92 mm and 46 x 92 mm	UA6P	●		
	Hole punch adapter for holes to 144 mm dia., 138 x 138 mm and 68 x 138 mm	UA12P		●
 Die for punching DIN rails 35 x 15; 32 x 15 x 9; 35 x 7.5	UPD6	●		