



Crimping

Battery powered hydraulic crimping tools

EK 60/22 Battery powered hydraulic crimping tool 6 - 300 mm²

**NEXT
GENERATION**



- ▶ Large crimping range up to 300 mm²
- ▶ Fast crimp cycles due to Automatic Retraction Stop (ARS)
- ▶ All tool data in view thanks to display and i-press® app

Characteristics

- Choose your battery system: Bosch or Makita
- All data can be easily read via Bluetooth
- Closed head, flip top style, rotatable
- Quality assurance via visual and audible signals in case of error
- Simple and safe: One-button operating concept for controlling all tool functions
- Effortless working due to balanced centre of gravity
- LED for work area illumination
- Simple and safe: Automatic retraction when operation is complete
- Automatic retract stop (ARS) for positioning control in case of multiple crimps
- Always ready-to-use thanks to battery charge and service display

Suitable for

- 22-series interchangeable dies, narrow crimping



Technical data			
Crimping force	60 kN		
Hub	17 mm		
Crimping range	6 - 300 mm ²		
Crimping cycle	3 s to 5 s (depending on crimp cross-section)		
Charging time	45 min.		
Weight incl. battery	4.4 kg		
Ambient temperature	-10 °C up to +40 °C		
Item	Part No. Bosch	Part No. Makita	
Battery powered hydraulic crimping tool 6 - 300 mm ²	EK6022CFB	EK6022CFM	
Scope of supply			Page
Bosch battery 18 V / 5.0 Ah, Li-Ion	RALB2EU		485
Bosch quick-charger for 18 V Li-Ion battery	LGLB1EU		486
Makita battery 18 V / 4.0 Ah, Li-Ion		RAL40	484
Makita quick-charger for 18 V Li-Ion battery		LGL1	486
Plastic case	KK120NG	KK120NG	
Accessories			Page
Bosch battery 18 V / 5.0 Ah, Li-Ion	RALB2EU		485
Makita battery 18 V / 4.0 Ah, Li-Ion		RAL40	484
Item		Part No.	Page
EK 60/22 with crimping die set D 22 from 16 - 240 mm ²		EK6022CFMSETD	
EK 60/22 with crimping die set R 22 from 16 - 240 mm ²		EK6022CFMSETR	