## K 105/1 Hand-operated cutting tool for Al and Cu cables to 26 mm with telescopic handles dia.



- ▶ Compact dimensions with extending telescopic handles for easier carrying
- ▶ High cutting performance
- ▶ Also for fine-stranded conductors e.g. to DIN EN 60228 Cl. 5

## **Characteristics**

- Two-hand operation
- Maintenance on-site due to replacement of cutting heads
- Safe working thanks to roughened handle
- Not suitable for cutting steel or steel wire

Technical data			
Cutting range	e.g. 4 x 25 mm² NYY, max. 26 mm dia.		
Length	Stepless 350 - 520 mm		
Weight	1.4 kg		
Item		Part No.	
Hand-operated cutting tool for Al and Cu cables to 26 mm dia., length 350 - 520 mm continuous		K1051	
Accessories		Part No.	Page
Replacement cutting head		K1011E	

## K 201/1 Hand-operated cutting tool for Al and Cu cables to 26 mm dia., length 570 mm





- ▶ 1000 V fully insulated to IEC 60900
- ► High cutting performance
- ▶ Also for fine-stranded conductors e.g. to DIN EN 60228 CI. 5

## **Characteristics**

- Two-hand operation
- Maintenance on-site due to replacement of cutting heads
- · Not suitable for cutting steel or steel wire

Technical data			
Cutting range	max. 26 mm dia., e.g. 4 x 95 mm <sup>2</sup> NYY		
Length	570 mm		
Weight	2 kg		
Item		Part No.	
Hand-operated cutting tool for Al and Cu cables to 26 mm dia., length 570 mm		K2011	
Accessories		Part No.	Page
Replacement cutting head		K1011E	



