

28604.4

KDS-Set 8/16 BK



Cable entry set, IP66, Consisting of: 1 x KDS-SR 8/16, 1 x KDS-Inlay 1, 2 x KDS-Inlay 4

RAL: 9005

Business data

Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	66.79 g
Weight per piece (including packaging)	93.59 g
Unit of weight	G
Customs number	39259020
Country of origin	DE
Product description	Cable Entry

Technical data

Dimensions

Length	126 mm
Length of wall cutout	91 mm
Width	70 mm
Width of wall cutout	46 mm
Height	19.6 mm
Installation height	19.6 mm
Diameter of the screw holes	5.5 mm

Materials

Material	Polyamide 6.6
Glass-fibre reinforced	✓
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	120 °C
Sealing material	Polyurethane-based
Type of seal	Sealing and moulded flexible foam
Halogen-free	✓
Silicone-free	✓

Further technical data

Mounting type	Screws
Degree of protection	IP66
NEMA Type	4x indoor use only
Number of screw holes	4
Fixing screws	M 5 (ISO 4762 / DIN 912)
Torque of the fixing screws	3 Nm

Print

Colour	Black
--------	-------

Technical data

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2022-01-17
REACH Candidate Substance Note	No
RoHS Conform	yes

28604.4

KDS-Set 8/16 BK

Approvals

UL Recognized

UL File Number	E489821
----------------	---------

UL approval	UL 508A
-------------	---------

UL Recognized	yes
---------------	-----

cUL Recognized

cUL File Number	E489821
-----------------	---------

cUL approval	C22.2 No. 14-18
--------------	-----------------

cUL Recognized	yes
----------------	-----

Media

