



Short-circuit plug, No. of poles: 2, Mounting type: Plug in, Width: 14.3 mm, Rated cross-section: 6 mm<sup>2</sup>, Colour: Yellow

**RAL:** 1026

### Business data

|  |                    |
|--|--------------------|
| Article number                             | 17552.8            |
| Article name                               | KS-SQI 6/2 YE      |
| GTIN (EAN)                                 | 4044211209193      |
| Colour                                     | Yellow             |
| Packaging unit                             | 50                 |
| Quantity unit                              | PC                 |
| Weight per piece (not including packaging) | 3.24 g             |
| Weight per piece (including packaging)     | 3.34 g             |
| Unit of weight                             | G                  |
| Customs number                             | 85389099           |
| Country of origin                          | DE                 |
| Product description                        | Short-circuit plug |

### Technical data

#### Dimensions

|            |         |
|------------|---------|
| Length     | 10 mm   |
| Width      | 14.3 mm |
| Height     | 36.7 mm |
| Pitch size | 8.1 mm  |

#### Ratings

|                                 |                   |
|---------------------------------|-------------------|
| Voltage with partition, max.    | 1000 V            |
| Voltage without partition, max. | 1000 V            |
| Rated current                   | 41 A              |
| Current load, max.              | 41 A              |
| Rated cross-section             | 6 mm <sup>2</sup> |
| Contamination degree            | 2                 |

#### Connection data

|              |   |
|--------------|---|
| No. of poles | 2 |
|--------------|---|

#### Materials

|                           |               |
|---------------------------|---------------|
| Material                  | Copper alloy  |
| Insulation housing        | Polyamide 6.6 |
| Flammability class UL 94  | V-2           |
| Working temperature, min. | -40 °C        |
| Working temperature, max. | 105 °C        |

#### Further technical data

|                               |         |
|-------------------------------|---------|
| Mounting type                 | Plug in |
| Insulation available          | ✓       |
| Touch protection is available | ✓       |
| Number of bridged terminals   | 2       |

#### Environmental Product Compliance

|                                |            |
|--------------------------------|------------|
| REACH Conform                  | yes        |
| REACH Reference date           | 2022-06-10 |
| REACH Candidate Substance Note | No         |
| RoHS Conform                   | yes        |

---


### Media

---

### Accessories


#### ##INVERSE##CONTA-CONNECT

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm<sup>2</sup>, Width: 8.1 mm, Colour: Beige



| Article number          | Article name    | GTIN (EAN)    | Packaging unit |
|-------------------------|-----------------|---------------|----------------|
| <a href="#">17523.2</a> | SPTK 6/LT/HB BG | 4044211209223 | 50 ST          |

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm<sup>2</sup>, Width: 8.1 mm, Colour: Beige



| Article number          | Article name         | GTIN (EAN)    | Packaging unit |
|-------------------------|----------------------|---------------|----------------|
| <a href="#">17524.2</a> | SPTK 6/LT/STBI/YE BG | 4044211209919 | 50 ST          |

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm<sup>2</sup>, Width: 8.1 mm, Colour: Beige



| Article number          | Article name | GTIN (EAN)    | Packaging unit |
|-------------------------|--------------|---------------|----------------|
| <a href="#">17520.2</a> | SPTK 6/DU BG | 4044211209650 | 50 ST          |

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm<sup>2</sup>, Width: 8.1 mm, Colour: Beige



| Article number          | Article name | GTIN (EAN)    | Packaging unit |
|-------------------------|--------------|---------------|----------------|
| <a href="#">17521.2</a> | SPTK 6/LT BG | 4044211209162 | 50 ST          |

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm<sup>2</sup>, Width: 8.1 mm, Colour: Beige



| Article number          | Article name | GTIN (EAN)    | Packaging unit |
|-------------------------|--------------|---------------|----------------|
| <a href="#">17522.2</a> | SPTK 6/QT BG | 4044211209216 | 50 ST          |


Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm<sup>2</sup>, Width: 8.1 mm, Colour: Beige



| Article number          | Article name         | GTIN (EAN)    | Packaging unit |
|-------------------------|----------------------|---------------|----------------|
| <a href="#">17525.2</a> | SPTK 6/LT/STBI/BU BG | 4044211209926 | 50 ST          |

#### ##INVERSE##CONTA-CONNECT

## 17552.8 KS-SQI 6/2 YE



Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5,  
Rated cross-section: 6 mm<sup>2</sup>, Width: 8.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN)    | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>17521.2</u> | SPTK 6/LT BG | 4044211209162 | 50 ST          |