



## Building Installation Connector System AC 166®

### G Cord Set

## AC 166 G VLC/315 SW 200 H5Z1 SW Dca



connection cable, 3 pole, black, coding: 1 (mains), cable type: H05Z1Z1-F, core cross-section: 1.5 mm<sup>2</sup>, Fire Class: Dca, length: 2.00 m, voltage rating: 250 V, current rating: 16.0 A

### Order Info

<b>reference number (ref. no.)</b>	96476320
<b>PU</b>	50
<b>EAN</b>	4028012112135

### Type

<b>type</b>	connection cable
<b>number of poles</b>	3 pole
<b>colour</b>	black
<b>coding</b>	1 (mains)
<b>PE function</b>	yes
<b>protection against incorrect plugging</b>	yes

### Technical Data

<b>voltage rating</b>	250 V
<b>current rating</b>	16.0 A
<b>insulating material</b>	PA 6.6
<b>contact material</b>	brass
<b>max. Ambient Temperature Operation</b>	70 °C
<b>IP code</b>	IP20
<b>IP code when plugged</b>	IP40
<b>type of conductor flexible</b>	yes
<b>cable type</b>	H05Z1Z1-F
<b>core cross-section</b>	1.5 mm <sup>2</sup>
<b>Fire Class</b>	Dca
<b>length</b>	2.00 m

### Accessories

<b>AC 166 VSF SW</b>	169563
<b>AC 166 VSF WS</b>	169553