

Junction Box

Sd 7-L



Sd 7-L

Junction Box

Productnumber: 33290701

Dimensions: 75 x 75 x 37 mm

Junction Box, with protection class IP55, Nominal cross-section 2,5 mm², Ui=400V AC, certified according to VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), Self-sealing insertion membranes, Sealing area 8,2 - 12,5 mm, (3 Rear, 7 Side), Internal fastening points, for standard indoor installations

grey, without terminals



Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V
Protection type UL:	not specified
Type of protection:	IP55
Max. conductor cross section:	2,5 mm ²
Protection class:	II

Colours

Base unit colour:	grey
Cover colour:	grey

Dimensions

Width:	75 mm
Length:	75 mm

Dimensions

Height:	37 mm
---------	-------

Material characteristics

suitable for exterior use:	no
Flammability class according with UL94:	HB
Glow-wire flammability according to EN 60695-2-11:	650 °C
Halogen free:	yes
Industry quality:	no

mechanical properties

for sealing range max:	12.5 mm
Type of fastening:	Wall/ceiling mounting
Sealable:	no
for sealing range min:	8.2 mm
Impact strength:	IK07

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Material

Base unit material:	Polypropylene
Cover material:	Polypropylene

Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))
------------	---

Accessories

[30040701 - VST RR - Sealing plugs](#)