

## Installation housing

# IBTLED 3

## IBTLED 3

### Installation housing

Productnumber: 98220001

Dimensions: 277 x 400 x 165 mm

Installation housing, for prefabricated construction, halogen-free, for the installation of LV/HV/LED lights and speakers, announcement and call systems, for the installation of VDE-tested lights to DIN EN 60598 (VDE 0711), and with F or MM marking, with protection class IP30, Rated insulation voltage: 400V AC, Halogen free

**maximum installation depth for luminaires, speakers, announcement and call systems: 130 mm, lamp output halogen max. 100 W, lamp output, LED max. 47 W, additional inserts 8 x to M40, Outlet aperture: Fermacell® board, variable up to max. 200 x 300 mm, 8 combi-conduit entries 4 x M20, M25, 4 x M25, integrated conduit stopper and strain relief for M20, M25 conduits, adhesive fixing or nail installation, combination conduit insertion and membrane for perforation, Sealing area M16 - M40**



## Technical Data

### electrical characteristics

Rated insulation voltage AC:	400 V
Type of protection:	IP30
Suitable for:	Concrete construction

### Colours

Base unit colour:	grey
Cover colour:	green

### Dimensions

Width:	277 mm
--------	--------

## Dimensions

Length:	400 mm
Height:	165 mm
Inner length:	300 mm
Inner width:	200 mm
Inner height:	155 mm

## Material characteristics

Industry quality:	no
Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability according to EN 60695-2-11:	650 °C

## mechanical properties

Type of fastening:	adhesive fixing or nail installation
--------------------	--------------------------------------

## Ambient conditions

max. relative humidity 25°C:	- %
------------------------------	-----

max. relative humidity 40°C:	50 %
------------------------------	------

Min. ambient temperature:	-25 °C
---------------------------	--------

Max. ambient temperature:	60 °C
---------------------------	-------

24h ambient temperature:	35 °C
--------------------------	-------

## Material

Base unit material:	Polypropylene
---------------------	---------------

Cover material:	Polypropylene
-----------------	---------------