









Clamp terminal 95-185mm<sup>2</sup>, for 20x5-30x10

Part no. **AKS185**  
 Catalog No. **107195**

EL-Nummer (Norway) **2465033**

### Delivery program

Product range			60 mm system 185 mm system
Basic function			Connections
Subrange			Clamp terminals
Description			Termination to busbars without drilling A cable block is used to connect the conductor to the busbar
Width		mm	38
Rated operational current	$I_e$	A	500
conductor			95 - 185 mm <sup>2</sup> AWG3/0 - MCM350. directly terminated:   
Cu factor		kg	0,00
For use with			20 x 5/10 25 x 5/10 30 x 5/10
For use with			Double T profile
<b>Notes</b>			
○ round conductor, solid			
 Flexible, round conductor with correctly crimped ferrule			
Round conductor, stranded			
 Sector conductor, solid			
Sector conductor, stranded			
# CU band			
 CU busbar			

### Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)			
Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ecl@ss10.0.1-27-14-11-46 [BAA025013])			
Busbar thickness		mm	5 - 10
Busbar width		mm	20 - 30
Suitable for			Flat rail
Width clamp		mm	38
Max. conductor cross section		mm <sup>2</sup>	185
Max. rated operation current $I_e$		A	500
Suitable for round conductor connection			Yes
Suitable for sector conductor connection			Yes
Suitable for strip conductor connection			Yes

### Approvals

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37

North America Certification		UL recognized, CSA certified
Conditions of Acceptability		Refer to approbation report
Specially designed for North America		No
Suitable for		Feeder circuits
Current Limiting Circuit-Breaker		Refer to approbation report
Max. Voltage Rating		600 V AC
Degree of Protection		Feeder circuits

## Dimensions

