


SRS IT cabinets


Basic version ensures optimum installation and configuration. Welded structure ensures safety of use even at maximum load. Used primarily as a network cabinet/distribution point.



Additional side cable grommets on the base and on the cabinet roof allowing perfect cable arrangement outside the 19" space (for cabinets with a width of 800mm).



Installation height numbering as a standard



Dedicated place on the cabinet base for provision of earth strip (not included in delivery)



All removable elements (doors, side and rear cover) have earth cords

Available dimensions

Type	Width (mm)	Depth (mm)	Height (mm)	Door front	Door rear	Index RAL7035
15U	600	600	780	2	6	SRS1560602611.1
		800	780	2	6	SRS1560802611.1
	800	800	780	2	6	SRS1580802611.1
18U	600	600	915	2	6	SRS1860602611.1
		800	915	2	6	SRS1860802611.1
	800	800	915	2	6	SRS1880802611.1
22U	600	600	1095	2	6	SRS2260602611.1
		800	1095	2	6	SRS2260802611.1
	800	800	1095	2	6	SRS2280802611.1
24U	600	600	1210	2	6	SRS2460602611.1
		800	1210	2	6	SRS2460802611.1
	800	800	1210	2	6	SRS2480802611.1
27U	600	600	1315	2	6	SRS2760602611.1
		800	1315	2	6	SRS2780802611.1
	800	800	1315	2	6	SRS2780802611.1

Type	Width (mm)	Depth (mm)	Height (mm)	Door front	Door rear	Index RAL7035
32U	600	600	1535	2	6	SRS3260602611.1
		800	1535	2	6	SRS3260802611.1
	800	800	1535	2	6	SRS3280802611.1
42U	600	600	1980	1	6	SRS4260601611.1
		600	1980	2	6	SRS4260602611.1
		800	1980	1	6	SRS4260801611.1
		800	1980	2	6	SRS4260802611.1
	800	800	1980	1	6	SRS4280801611.1
		800	1980	2	6	SRS4280802611.1
45U	600	600	2120	2	6	SRS4560602611.1
		800	2120	2	6	SRS4560802611.1
	800	800	2120	2	6	SRS4580802611.1
47U	600	600	2186	2	6	SRS4760602611.1
		800	2186	2	6	SRS4760802611.1
	800	800	2186	2	6	SRS4780802611.1

* other configurations available on request

Basic parameters:

- Material: steel sheet
- Front door: sheet metal/glass or full glazing
- Rear door: shortened sheet metal wall
- Side walls: steel sheet
- Load capacity: 600 kg
- IP rating: 20
- Colour: RAL7035

Maximum spacing of mounting sections depending on cabinet depth:

- cabinets with a depth of 600 mm - maximum spacing: 472 mm
- cabinets with a depth of 800 mm - maximum spacing: 672 mm
- cabinets with a depth of 900 mm - maximum spacing: 772 mm

Regulatory compliance:

EIA-310-D, IEC 60297-1, IEC 60297-2, ROHS

Included in delivery:

- brush strip
- set of M6 assembly bolts (16 pcs)
- set of floor-leveler feet
- 1,5 m edge sealing
- 2 pairs of 19" mounting sections

