

PVC insulated spade terminals

Maximum electrical rating : 600 V max.
 Maximum temperature : 75 °C
 Insulation material : PVC
 Terminal material : Copper

Also available without sleeve and with "easy entry"



Typenr.	Color	Wire range (mm ²)	Groove (mm)	AWG	Length (mm)	Packing (pcs)
V 3.2 r	Red	0,5 ~ 1,5	3,2	22 ~ 16	21,0	100
V 3.7 r	Red	0,5 ~ 1,5	3,7	22 ~ 16	20,6	100
V 4.3 r	Red	0,5 ~ 1,5	4,3	22 ~ 16	20,6	100
V 5.3 r	Red	0,5 ~ 1,5	5,3	22 ~ 16	21,0	100
V 6.4 r	Red	0,5 ~ 1,5	6,5	22 ~ 16	27,2	100
V 3.7 b	Blue	1,5 ~ 2,5	3,7	16 ~ 14	21,0	100
V 4.3 b	Blue	1,5 ~ 2,5	4,3	16 ~ 14	21,0	100
V 5.3 b	Blue	1,5 ~ 2,5	5,3	16 ~ 14	22,0	100
V 6.4 b	Blue	1,5 ~ 2,5	6,5	16 ~ 14	27,2	100
V 8.4 b	Blue	1,5 ~ 2,5	8,4	16 ~ 14	27,2	100
V 3.7 g	Yellow	4,0 ~ 6,0	3,7	12 ~ 10	25,2	100
V 4.3 g	Yellow	4,0 ~ 6,0	4,3	12 ~ 10	25,2	100
V 5.3 g	Yellow	4,0 ~ 6,0	5,3	12 ~ 10	25,2	100
V 6.4 g	Yellow	4,0 ~ 6,0	6,5	12 ~ 10	31,2	100