



Your Personal Connection

# 4.0 Terminals

## PVC insulated ring terminals

Maximum electrical rating : 600 V max.  
 Maximum temperature : 75 °C  
 Insulation material : PVC  
 Terminal material : Copper

Also available without sleeve and with "easy entry"



Typenr.	Color	Wire range (mm <sup>2</sup> )	Hole (mm)	AWG	Length (mm)	Packing (pcs)
R 3.2 r	Red	0,5 ~ 1,5	3,2	22 ~ 16	18,0	100
R 3.7 r	Red	0,5 ~ 1,5	3,7	22 ~ 16	19,9	100
R 4.3 r	Red	0,5 ~ 1,5	4,3	22 ~ 16	19,9	100
R 5.3 r	Red	0,5 ~ 1,5	5,3	22 ~ 16	21,3	100
R 6.4 r	Red	0,5 ~ 1,5	6,4	22 ~ 16	27,3	100
R 8.4 r	Red	0,5 ~ 1,5	8,4	22 ~ 16	27,3	100
R 10.5 r	Red	0,5 ~ 1,5	10,5	22 ~ 16	31,0	100
R 3.7 b	Blue	1,5 ~ 2,5	3,7	16 ~ 14	19,9	100
R 4.3 b	Blue	1,5 ~ 2,5	4,3	16 ~ 14	22,3	100
R 5.3 b	Blue	1,5 ~ 2,5	5,3	16 ~ 14	22,3	100
R 6.4 b	Blue	1,5 ~ 2,5	6,4	16 ~ 14	27,3	100
R 8.4 b	Blue	1,5 ~ 2,5	8,4	16 ~ 14	27,3	100
R 10.5 b	Blue	1,5 ~ 2,5	10,5	16 ~ 14	31,0	100
R 3.7 g	Yellow	4,0 ~ 6,0	3,7	12 ~ 10	23,2	100
R 4.3 g	Yellow	4,0 ~ 6,0	4,3	12 ~ 10	27,1	100
R 5.3 g	Yellow	4,0 ~ 6,0	5,3	12 ~ 10	27,1	100
R 6.4 g	Yellow	4,0 ~ 6,0	6,4	12 ~ 10	30,0	100
R 8.4 g	Yellow	4,0 ~ 6,0	8,4	12 ~ 10	34,5	100
R 10.5 g	Yellow	4,0 ~ 6,0	10,5	12 ~ 10	34,5	100