

PVC insulated butt connectors

Maximum electrical rating : 600 V max.
 Maximum temperature : 75 °C
 Insulation material : PVC
 Terminal material : Copper



Typenr.	Color	Wire range (mm ²)	Length (mm)	AWG	Packing (pcs)
Ver 1.25 r	Red	0,5 ~ 1,5	26,0	22 ~ 16	100
Ver 2 b	Blue	1,5 ~ 2,5	26,0	16 ~ 14	100
Ver 5.5 g	Yellow	4,0 ~ 6,0	26,0	12 ~ 10	100

Heat shrinkable butt connectors

Properties : 100% waterproof with heat shrinkable tubing
 Temperature range : -10 °C up to +105 °C
 Shrink temperature : +100 °C up to +200 °C
 Insulation material : Polyolefin
 Certification : RoHS



Typenr.	Color	Wire range (mm ²)	Length (mm)	AWG	Packing (pcs)
Ver 1.25 r heat shrink	Red	0,5 ~ 1,5	37,0	22 ~ 16	100
Ver 2 b heat shrink	Blue	1,5 ~ 2,5	37,0	16 ~ 14	100
Ver 5.5 g heat shrink	Yellow	4,0 ~ 6,0	41,0	12 ~ 10	100