

1

2

3

4

5

index

## RK ..X..

- distribution trunking




MAT PVC


-20 - +60°C  
 A1 - F  
 30 sec.

- Optimal closing, fixed cover.
- Easy installation and removal.
- Trunkings are supplied with cover.
- Rib can be easily broken out at the bottom of the trunking.
- For construction height 60 mm and above there are shaped ribs.
- Rib width 5,5 mm, cut-out width 4,5 mm.

item				L		EAN	number of conductors when 50 % of the trunking capacity is filled		
		w x h (mm)	w x h (mm)	(m)	(m)		0,75 mm <sup>2</sup> Ø 2,8 mm	1 mm <sup>2</sup> Ø 2,9 mm	1,5 mm <sup>2</sup> Ø 3,2 mm
RK 30X30_LD		30 x 30	27 x 27	2	64	<a href="#">8595057623132</a>	53	50	41
RK 30X40_LD		30 x 40	27 x 37	2	60	<a href="#">8595057623149</a>	105	98	80
RK 40X60_LD		40 x 60	36 x 56	2	48	<a href="#">8595057623187</a>	162	151	124
RK 60X60_LD		60 x 60	56 x 56	2	36	<a href="#">8595057623194</a>	245	229	188
RK 80X60_LD		80 x 60	76 x 56	2	32	<a href="#">8595057623200</a>	333	310	255
RK 100X60_LD		100 x 60	96 x 56	2	22	<a href="#">8595057623217</a>	417	389	319
RK 40X80_LD		40 x 80	36 x 76	2	40	<a href="#">8595057623248</a>	231	216	177
RK 60X80_LD		60 x 80	56 x 76	2	36	<a href="#">8595057623255</a>	350	326	268



The perforation is in one row up to the width of 60 mm.



The perforation in two rows above the width of 80 mm.

## Accessories to distribution trunkings

								EAN
				mm	mm	pcs	m	
		flexible conductor trunking (installation by means of bonding tape)		RK-OVK20_LA RK-OVK30_LB RK-OVK40_LB	500 500 500	20 30 40	60 36 24	<a href="#">8595057623811</a> <a href="#">8595057623828</a> <a href="#">8595057623835</a>
		spiral tube		RK-ST6_H25 RK-ST12_H20 RK-ST22_H25		4 9 16		<a href="#">8595057623842</a> <a href="#">8595057623859</a> <a href="#">8595057623866</a>
		fixing rivers (to fix the canal to the underlying material)		RK-PN6_FA		6	4000	<a href="#">8595057623927</a>

material

fire reaction class of underlying material

temperature resistance

self-extinguishing

color

dimensions - height, width

inner dimensions - height, width

length

outside diameter

package