

7.0 Other fixation materials

Braided sleeving

Material : Polyester PET HB
Temperature range : -50 °C up to +150 °C
Melting temperature : +250 °C

Melting temperature : +250 °Color : Black



Typenr.	Bundle diameter (mm)	Packing (mtr)
Braided sleeving PG 3 mm	3,00 - 7,00	100
Braided sleeving PG 4 mm	4,00 - 10,00	100
Braided sleeving PG 5 mm	5,00 - 10,00	100
Braided sleeving PG 8 mm	8,00 - 11,00	100
Braided sleeving PG 10 mm	10,00 - 15,00	100
Braided sleeving PG 12 mm	12,00 - 19,00	50
Braided sleeving PG 15 mm	15,00 - 27,00	50
Braided sleeving PG 20 mm	20,00 - 28,00	50
Braided sleeving PG 25 mm	25,00 - 34,00	25
Braided sleeving PG 30 mm	30,00 - 37,00	25
Braided sleeving PG 40 mm	40,00 - 45,00	25
Braided sleeving PG 50 mm	50,00 - 65,00	25

Wrapping bands

Material : Polyethylene
Temperature range : -50 °C up to +85 °C
Colors : Black and natural





Typenr.	Inside diameter (mm)	Outside diameter (mm)	W (mm)	Bundle diameter (mm)	Packing (mtr)
GST-4	5,0	6,0	7,0	4,0 - 50,0	10,0
GST-6	7,0	8,0	10,8	6,0 - 60,0	10,0
GST-8	8,5	10,0	11,4	7,5 - 60,0	10,0
GST-9	10,2	12,0	13,9	9,0 - 65,0	10,0
GST-12	13,0	15,0	15,0	12,0 - 70,0	10,0
GST-15	16,4	19,0	18,2	15,0 - 100,0	10,0
GST-20	21,0	24,0	19,6	20,0 - 130,0	10,0