



IBTLED 2



IBTLED 2

Installation housing

227 x 250 x 135 mm
Article number: 98215001

Universal mounting enclosure, for prefabricated construction, Halogen-free, for installing NV/HV/LED luminaires and loudspeakers., as well as messaging and call systems, Suitable for adhesive fixing, For the installation of VDE-approved lights per DIN EN 60598 (VDE 0711), as well as with F identification or MM identification, maximum installation height for lamps, loudspeakers, messaging and call systems: 100 mm, {Lampenleistung Halogen max. 50 W}, Lamp output LED max. 20 W

outlet aperture: Fermacell® plasterboard, Variable up to max. 150 x 150 mm, 8 combi-conduit entry points 4 x M20, 4 x M25 integrated conduit stopper and strain relief for conduits M20, M25



Technical data

Measures

Width:	227 mm
Length:	250 mm
Height:	135 mm
Inner height:	125 mm
Inner width:	150 mm
Inner length:	150 mm

Material:

material:	Polypropylene
Box:	Polypropylene
Cover:	Polypropylene

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 40° C:	50%
Ambient temperature (max.):	60 °C



INSTALLATION HOUSING

IBTLED 2

Other attributes

Color:	Grey
Ingress protection:	IP30 - acc. EN 60529 / DIN VDE 0470-1
