



INSTALLATION HOUSING

IBTLED 1



IBTLED 1

Installation housing

177 x 200 x 135 mm
Article number: 98210001

Universal mounting enclosure, for prefabricated construction, Halogen-free, for installing NV/HV/LED luminaires and loudspeakers., as well as messaging and call systems, Suitable for adhesive fixing, For the installation of VDE-approved lights per DIN EN 60598 (VDE 0711), as well as with F identification or MM identification, maximum installation height for lamps, loudspeakers, messaging and call systems: 100 mm, {Lampenleistung Halogen max. 25 W}, Lamp output LED max. 15 W

outlet aperture: Fermacell® plasterboard, Variable up to max. 100 x 100 mm, 8 combi-conduit entry points 4 x M20, 4 x M25 integrated conduit stopper and strain relief for conduits M20, M25



Technical data

Measures

| | |
|---------------|--------|
| Width: | 177 mm |
| Length: | 200 mm |
| Height: | 135 mm |
| Inner height: | 125 mm |
| Inner width: | 100 mm |
| Inner length: | 100 mm |

Material:

| | |
|-----------|---------------|
| Box: | Polypropylene |
| Cover: | Polypropylene |
| material: | Polypropylene |

Environmental attributes

| | |
|---|--------|
| Max. rel. humidity at 25° C (short term): | - |
| Ambient temperature (min.): | -25 °C |
| Ambient temperature (24 h): | 35 °C |
| Max. rel. humidity at 40° C: | 50% |
| Ambient temperature (max.): | 60 °C |