

wallbe® Pro

# THE FLEXIBLE ALL-ROUNDER



## Highlights

- › for private, semi-public and public use
- › variants with up to 22kW 32A 400V AC
- › incl. Schuko-Socket or socket type 23 (CH)
- › integration into payment-systems possible
- › integration into wallbe® Cloud possible
- › pre-wired and installation ready
- › individual designs on request

wallbe® stands for flexibility and usability. A full-metal casing makes the wallbe® Pro suited for a variety of different use cases. Wall-mounted or free-standing on a pillar, the pre-built mounting plates and foundations ensure an easy and cost efficient installation.

wallbe® Pro is suited for private, public and semi-public use at companies and institutions of all kinds. To achieve that flexibility the charger is available with different authorization methods ranging from key switches and RFID-technology to Smartphone-Apps.

wallbe® Pro

# STANDARD COMPLIANT, RELIABLE AND SECURE

## Advantages

- > made in Germany
- > option: variant conforming to calibration rights
- > compact, weatherproof construction
- > quick installation
- > easy to use
- > comfortable cable routing
- > flexibly scalable
- > high security standards



Illustrations do not correspond to the standard version

## Technical details wallbe® Pro

Charging cable / Socket	Standard: Type 2 socket Optional: Tethered cable Type 2 or Type 1
Charge performance	Variants: from 3,7kW to 22kW 16A 1-phase 230V to 32A 3-phase 400V
Authorization	Standard: ON/OFF Button Optional: Key switch, RFID, APP
Interfaces	Standard: Ethernet RJ45 & Modbus RS485
Safety	RCM Module – DC residual current detection 6mA according to IEC61851 / Load contactor welding detection / Lock & Release Module – Safe removal of charge plug during power loss
Compliance	Standard compliant according to IEC 61851 Mode 3, CE compliant
Color	Standard: White Optional: Individual design
Dimensions / Weight	Wall-Box: H35cm x W35cm x D17cm, ca. 12kg Charging pole: H125cm x W56cm x D20cm, approx. 23 kg
Origin	Made in Germany – <a href="http://www.wallbe.de">www.wallbe.de</a>
Temperature / IP-Class	-20°C bis +55°C / IP 54

**wallbe®**

Paderborner Straße 76  
33189 Schlangen  
Tel.: +49 (0) 5252 98892-00  
[sales@wallbe.de](mailto:sales@wallbe.de)  
[www.wallbe.de](http://www.wallbe.de)

We and our certified partners are pleased to help you with any questions related to our wallbe® products as well as their installation. An overview of certified partners in your area can be found on [www.wallbe.de/en/partner](http://www.wallbe.de/en/partner)

